

# DECLARATION OF PERFORMANCE

No 02CSI-2017-EN

**1. Unique identification code of the product type:**

**CROSSIN ATTIC HARD Foam**

**2. Intended use/s:**

Thermal insulating products for buildings. For professional usage as an in-situ formed sprayed rigid polyurethane (PUR) foam for buildings and industrial objects.

**3. Manufacturer:**

PCC Prodex Sp. z o.o.

56-120 Brzeg Dolny

Ul. Henryka Sienkiewicza 4

**4. System of AVCP:**

System 3

**5. Harmonized standard:**

EN 14315-1:2013

**Notified body**

Nr 1488

Instytut Techniki Budowlanej

00-611 Warszawa,

Ul. Filtrowa 1

PCC PRODEX Spółka z o.o.  
Z-ca Kierownika  
Działu Badań i Rozwoju  
Tomasz Rączko



**6. Declared performance/s:**

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	<b>Klasa E</b>	EN 14315-1
Short-term water absorption by partial immersion, $W_p$	<b>0,11 kg/m<sup>2</sup></b>	EN 14315-1
Thermal conductivity, $\lambda$	$\lambda_{\text{mean,i}} = 0,021 \text{ W/mK}$ $\lambda_{90,90} = 0,022 \text{ W/mK}$	
Declared aged thermal conductivity, $\lambda_D$	<b>For thickness dN &lt; 40 mm</b> $\lambda_D = 0,027 \text{ W/mK}$ <b>For thickness 40 mm ≤ dN &lt; 60 mm</b> $\lambda_D = 0,025 \text{ W/mK}$ <b>For thickness dN ≥ 60 mm</b> $\lambda_D = 0,024 \text{ W/mK}$	EN 14315-1
Water vapour diffusion resistance factor, $\mu$	<b>MU35</b>	EN 14315-1
Compressive stress at 10% deformation, $\sigma_{10}$	<b>CS(10\Y)200</b>	EN 14315-1

**7. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.**

Signed for and on behalf of the manufacturer by:

Tomasz Rączko

at Żółwin, on 20.11.2017

Deputy of Research  
and Development Manager

PCC PRODEX Spółka z o.o.  
Z-ca Kierownika  
Działu Badań i Rozwoju  
Tomasz Rączko